

## RL5416DC

RICE LAKE DIGITAL CANISTER LOAD CELLS, IN STAINLESS STEEL,  
"RL5416DC" SERIES WITH CONNECTORS



Digital canister load cells for CE-M approved weighbridges, tanks, silos, etc. Manufactured in STAINLESS STEEL, IP68 protection degree, 4000 divisions.

Specifically developed for working without junction box.

**CAPACITIES:** 30 t, 40 t

**OIML R60. C4** precision class.

**Stainless steel** body. **IP68** Protection Degree.

h= 150 mm.

The best solution  
for advanced industrial  
applications

## • TECHNICAL FEATURES

### METROLOGICAL FEATURES

- Rated capacity: (FS): 30 t, 40 t
- Combined error: 0,02 %F.S
- Creep error (after 30 min.): 0,02 %FS
- Temperature effect on zero: 0,003 %F.S./°C
- Temperature effect on sensitivity: 0,0008 %F.S./°C

### OIML R60

- $V_{min} = E_{max}/18000$
- Accuracy class: C4
- Max. number of intervals: 4000e (EC Test Certificate, according to OIML R60 (2000))

### ELECTRONIC\MECHANICAL FEATURES

- Gas dischargers to protect against atmospheric discharges
- Double connector for load cells interconnection and weight indicator connection, without junction box.
- RS485 communication technology
- Rice Lake communication protocol
- Power Supply: 8...15 Vdc
- Rated digital output: 40000 d
- Current consumption: 35 mA
- Internal resolution: 24 bit
- Converter rate: max. 40 conv./sec.
- RS485 communication speed: Max 100kHz.
- Operating temperature: -20 ~ +70 °C
- Compensated temperature: -10 ~ +40 °C
- Safe load limit: 120% F.S.
- Ultimate overload: 150% F.S.
- IP68 protection degree
- Stainless steel body
- 4-core RS485 cable as optional, 7mm diameter
- Nickel plated steel cable gland
- Self-centring spherical bases
- Equipped with anti-rotation system, to be combined with 173793 cups for proper operation

## • CONNECTION

CABLE COLOR CODE	
RED	EXCITATION +
BLACK	EXCITATION -
GREEN	A+
WHITE	B-
METAL	Shield

## VERSIONS

### Available versions

Codice		Max (kg)
195843		30 000
195844		40 000



“YOUR WORLDWIDE PARTNER FOR WEIGHING,”

DINI ARGEO  
FRANCE sarl  
France

DINI ARGEO  
GMBH  
Germany

DINI ARGEO  
UK Ltd  
United Kingdom

DINI ARGEO WEIGHING  
INSTRUMENTS Ltd  
China

DINI ARGEO  
OCEANIA  
Australia



**COMPANY HEADQUARTERS**

Via Della Fisica, 20  
41042 Spezzano di Fiorano Modena • Italy  
Tel. +39.0536 843418

**SERVICE ASSISTANCE**

Via Dell'Elettronica, 15  
41042 Spezzano di Fiorano Modena • Italy  
Tel. +39.0536 921784

SALES AND TECHNICAL ASSISTANCE SERVICE