

## RL5426DC

RICE LAKE DIGITAL CANISTER LOAD CELLS, IN STAINLESS STEEL,  
"RL5426DC" SERIES WITH CONNECTORS



Digital canister load cells for CE-M approved weighbridges, tanks, silos, etc. Manufactured in STAINLESS STEEL, IP68 protection degree, 6000 divisions.

Specifically developed for working without junction box.

**CAPACITIES:** 30 t, 40 t

**OIML R60. C6** precision class.

**Stainless steel** body. **IP68** Protection Degree.

h= 118,5 mm.

The best solution  
for advanced industrial  
applications

## • TECHNICAL FEATURES

### METROLOGICAL FEATURES

- Rated capacity: (FS): 30 t, 40 t
- Combined error: 0,015 %F.S
- Creep error (after 30 min.): 0,01 %FS
- Temperature effect on zero: 0,01 %F.S./5°C
- Temperature effect on sensitivity: 0,004 %F.S./5°C

### OIML R60

- $V_{min} = E_{max}/18000$
- Accuracy class: C6
- Max. number of intervals: 6000e (EC Test Certificate, according to OIML R60 (2000))

### ELECTRONIC\MECHANICAL FEATURES

- Gas dischargers to protect against atmospheric discharges
- Double connector for load cells interconnection and weight indicator connection, without junction box.
- RS485 communication technology
- Rice Lake communication protocol
- Power Supply: 8÷15 Vdc
- Rated digital output: 60000 d
- Current consumption: 35 mA
- Internal resolution: 24 bit
- Converter rate: max. 40 conv./sec.
- RS485 communication speed: Max 100kHz.
- Operating temperature: -35 ~ +70 °C
- Compensated temperature: -10 ~ +40 °C
- Normal service: 120% F.S.
- Maximum load / Safe load: 150% F.S.
- Ultimate overload: 300% F.S.
- IP68 protection degree
- Stainless steel body
- 4-core RS485 cable as optional, 7mm diameter
- Nickel plated steel cable gland
- Self-centring spherical bases
- Equipped with anti-rotation system, to be combined with 173798 cups for proper operation

## • CONNECTION

CABLE COLOR CODE	
RED	EXCITATION +
BLACK	EXCITATION -
GREEN	A+
WHITE	B-
METAL	Shield

## VERSIONS

### Available versions

Codice		Max (kg)
195845		30 000
195846		40 000



“YOUR WORLDWIDE PARTNER FOR WEIGHING,”

**DINI ARGEO  
FRANCE sarl**  
France

**DINI ARGEO  
GMBH**  
Germany

**DINI ARGEO  
UK Ltd**  
United Kingdom

**DINI ARGEO WEIGHING  
INSTRUMENTS Ltd**  
China

**DINI ARGEO  
OCEANIA**  
Australia



**COMPANY HEADQUARTERS**

Via Della Fisica, 20  
41042 Spezzano di Fiorano Modena • Italy  
Tel. +39.0536 843418

**SERVICE ASSISTANCE**

Via Dell'Elettronica, 15  
41042 Spezzano di Fiorano Modena • Italy  
Tel. +39.0536 921784

SALES AND TECHNICAL ASSISTANCE SERVICE